

1. **Unique identifier of the product-type:**
DRY-PRESSED CERAMIC TILES WITH WATER ABSORPTION $E_b \leq 0,5\%$; Group Bla; UNGLAZED (UGL)
2. **Intended use or uses:**
CERAMIC TILES FOR TILING OF FLOORS AND WALLS, INDOOR AND/OR OUTDOOR, INCLUDING STAIRS, IN BUILDINGS AND INDUSTRIAL FACILITIES
3. **Manufacturer:**
CERRAD; ul. Radomska 49B; 27-200 Starachowice
4. **Authorised Representative:**
NOT APPLICABLE
5. **System or systems of assessment and verification of constancy of performance of the construction product:**
ASSESSMENT SYSTEM: 4
- 6a. **Harmonised standard:**
EN 14411:2012
Notified body or bodies:
NOT APPLICABLE
- 6b. **European Assessment Document:**
NOT APPLICABLE
European Technical Assessment:
NOT APPLICABLE
Technical Assessment Body:
NOT APPLICABLE
Notified body or bodies:
NOT APPLICABLE

7. Declared performance

Essential characteristics	Performance
Reaction-to-fire performance	A1 _{fl} / A1
Hazardous materials release – glazed tiles	NPD – no performance determined
Breaking force	≥ 1300 N
Bond / adhesion strength for	-
- cement adhesives	$\geq 0,5$ N/mm ²
- dispersion adhesives	≥ 1 N/mm ²
- reactive resin adhesives	≥ 2 N/mm ²
- mortar	NPD – no performance determined
Slip resistance acc.to CEN/TS 16165:2016, Annex B	R10
Thermal shock resistance	pass
Durability, for:	-
- indoor use:	pass
- outdoor use, freeze thaw resistance	pass
Touch sensation	NPD – no performance determined

8. Relevant Technical Documentation and/or Specific Technical Documentation:

NOT APPLICABLE

The performance of the product referred to above is consistent with the set of declared performance/s.

This declaration of performance is issued in accordance with the Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer specified above.

Signed for and on behalf of the manufacturer by:

Dawid Ceglowski - Chief Operating Officer

Paweł Smolarek - Chief Product Officer

CZŁONEK ZARZĄDU
Dawid Ceglowski
Dawid Ceglowski

CZŁONEK ZARZĄDU
Paweł Smolarek
Paweł Smolarek

Starachowice, 01.03.2021