

DECLARATION OF PERFORMANCE

Nr 10/1 CPR

1. The unique identification code of the product type:

Dry- pressed ceramic tiles with low water absorption $E_b \leq 0,5\%$; Groupe BI_a, Unglazed (UGL)

2. Intended use or uses:

For internal and /or external floors and walls, including stairs, in buildings and industrial facilities

3. Manufacturer:

CERRAD Sp. z o.o.

ul. Radomska 49B

27-200 Starachowice

4. System(s) of assessment and verification of constancy of performance: **System 4**

5. Harmonised standard: **EN 14 411:2012**

6. Notified body or bodies: **Not applicable**

7. Declared performance

Essential Characteristics		Performance	Harmonised Technical Specification
Reaction-to-fire performance		A1 _{FL} /A1	EN 14 411:2012
Release of dangerous substances:		-	
- Cadmium		NPD	
- Lead		NPD	
- Others		NPD	
Breaking strength	thickness $\geq 7,5$ mm	≥ 1300 N	
Slippage according to CEN/TS 16165:2012, Annex B		NPD	
Bond strength/adhesion:		-	
- cementitious adhesives		$\geq 0,5$ N/mm ²	
- dispersion adhesives		≥ 1 N/mm ²	
- reaction resin adhesives		≥ 2 N/mm ²	
- mortar		NPD	
Thermal shock resistance		Pass	
Durability for:		-	
- internal use:		Pass	
- external use: resistance to freeze-thaw cycles		Pass	
Tactility		NPD	

8. Relevant Technical Documentation and/or Specific Technical Documentation:

NOT APPLICABLE

The performance characteristics of the aforementioned product comply with the set of declared performance properties. This Performance Declaration has been issued pursuant to the Regulation (EU) 305/2011 on the sole responsibility of the manufacturer indicated above.

Signed on behalf of the manufacturer:

Dawid Cegłowski - Chief Operating Officer



Paweł Smolarek -Chief Product Officer



Starachowice, 14.12.2021